

Configuration Line 1

Operation

Home

Address Book

Setup

Preferences

Speed Dial

Function Keys

Line 1

Line 2

Line 3

Line 4

Line 5

Line 6

Line 7

Action URL Settings

Advanced

Trusted Certificates

Software Update

Status

System Information

Log

SIP Trace

DNS Cache

PCAP Trace

Memory

Settings

Manual

Login

SIP

NAT

RTP

Login Information:

Displayname:

Account:

Password:

Registrar:

Authentication Username:

Mailbox:

Ringtone:

Custom Melody URL:

Display text for idle screen (max. 8 chars):

Save

0002*21

0002*21

pbx.pbospace.eu

0002*21

Ringer 1

PBXspace

snom

© 2000-2005 [snom AG](#)

Configuration Line 1

Operation

Home

Address Book

Setup

Preferences

Speed Dial

Function Keys

Line 1

Line 2

Line 3

Line 4

Line 5

Line 6

Line 7

Action URL Settings

Advanced

Trusted Certificates

Software Update

Status

System Information

Log

SIP Trace

DNS Cache

PCAP Trace

Memory

Settings

Manual

Login

SIP

NAT

RTP

SIP Line Settings:

Outbound Proxy:

Music on hold server:

Alert Info URL:

User picture URL:

Music on hold Streaming URL:

Dial-Plan String:

Proxy Require:

Q-Value:

Proposed Expiry:

Auto Answer:

Long SIP-Contact (RFC3840):

Support broken Registrar:

Save

10 mins

snom

© 2000-2005 [snom AG](#)

Configuration Line 1

Operation

Home

Address Book

Setup

Preferences

Speed Dial

Function Keys

Line 1

Line 2

Line 3

Line 4

Line 5

Line 6

Line 7

Action URL Settings

Advanced

Trusted Certificates

Software Update

Status

System Information

Log

SIP Trace

DNS Cache

PCAP Trace

Memory

Settings

Manual

Login

SIP

NAT

RTP

NAT Line Settings:

Offer ICE:

STUN server (IP-addr:port):

STUN binding interval (seconds):

Keepalive interval (seconds):

Symmetrical RTP:

Save

15

on

snom

© 2000-2005 [snom AG](#)

Configuration Line 1

Operation

Home

Address Book

Setup

Preferences

Speed Dial

Function Keys

Line 1

Line 2

Line 3

Line 4

Line 5

Line 6

Line 7

Action URL Settings

Advanced

Trusted Certificates

Software Update

Status

System Information

Log

SIP Trace

DNS Cache

PCAP Trace

Memory

Settings

Manual

Login

SIP

NAT

RTP

RTP Line Settings:

Codec 1:

Codec 2:

Codec 3:

Codec 4:

Codec 5:

Codec 6:

Codec 7:

Packet Size:

RTP Encryption:

Save

G.722

G.711a

G.711a

G.711a

G.711a

G.711a

G.711u

20 ms

on

snom

© 2000-2005 [snom AG](#)